

Printing ID cards has never been so easy

Max Brown


No: 95756756

Sample Address, Sample Street, District P05t Cod3

Matica's MC110 has been designed to simplify card issuance, thanks to its user friendly, 'plug & print' operation.

The MC110 is the ideal solution for establishing an in-house ID card issuance program and is widely used by membership organisations and small to medium sized businesses. Based on Matica's robust and reliable print engine, the MC110 prints vibrant, colorful cards every time.

Upgradable from single to dual-sided, the MC110 is also available with a contactless enoder for the issuance of smart cards for access and entry control.





MC110 delivers...

- ▶ High quality TruEdge 300dpi printing
- ▶ Up to 150 color cards per hour
- ▶ Single to dual-sided upgrade
- ▶ Robust, reliable build quality
- ► Contactless encoding option
- 2 years warranty



Ideal for...

▶ Mid to low volume card issuance

MC110

Specifications

Printer specifications

Print technology

Dye-sublimation, direct-to-card

Print resolution

300 x 300 dpi

Print area

TruEdge (CR-80 cards)

Print speed

- 150 cph (YMCKO single side, batch)
- · 850 cph (monochrome printing)

Single-sided / optional dual-sided

Printer memory

Communications interface

USB 2.0

Easy to use, plug and print operation

- 4 x LED status indicators
- Full front operation
- · Drop in ribbon cassette with easy handling
- · Automatic ribbon identification and setting
- · Easy reach power button
- · Easy maintenance access

Printer security

Support for Kensington® security lock

Printer dimensions (HxWxD)

256 x 202 x 405 mm / 10.6" x 7.9" x 15.9"

Weight

10 kg, 22 lbs

Power supply

- 220-240V/110-115V, 50-60 Hz
- Standby mode and reduced power consumption

Operating environment

- Temperature: 15°C 40°C, 59°F 104°F
- · Humidity: 20% 65% (non-condensing)

Storage conditions

- Temperature: -5°C to 70°C, 23°F to 158°F
- · Humidity: 20% to 70% (non-condensing)

Sound (ISO 7779)

Sound pressure less than 48dB (A)

Certifications

RoHs, CE, FCC, CQC, UL, WEEE, Proposition 65 (California, USA)

2 years (subject to the use of chromXpert® ribbons)

Card specifications

Input hopper capacity

· Batch: 100 cards (0.76 mm / 30 mil thickness)

Output hopper capacity

30 cards (front)

Card thickness

- 0.25 mm 1.25 mm / 10 mil 50 mil
- · Gauge adjustment

Card types

CR-80 PVC, PVC-C

Software specifications

XPS printer driver

Windows® (32/64bit) 7, 8.1, 10, 11, Server 2012,

Options

Contactless encoding

· ISO14443A, B, ISO15693, MIFARE®, DESFire®, HID iClass®


Dual-side activation kit

PR10300016



Consumables chrom // pert

- · To ensure print quality and card durability, printhead lifespan and overall printer reliability, use chromXpert ribbons only.
- · Supply cores and cassettes are recyclable. Packaging is recycled.



Part No.

Also available

ChromXpert™ ribbon program

· YMCKO (250 prints) PR20319301

· YMCKO-K (200 prints) PR20319302

PR20319303 (400 prints, half panel)

• KO (600 prints) PR20305304

· Monochrome K (2000 prints) PR20314305

· Monochrome: White, Red, Green, Blue, Scratch-off (1000 prints)

Cleaning kit PR20309601



Global offices

Europe: Switzerland HQ, Italy, UK and Germany

Asia: Malaysia, China and India

USA: Minneapolis HQ, South Carolina and San Francisco

Middle East: Dubai



are the property of their respective owners.

